

Schraubenschlüssel spanners and wrenches

Hakenschlüssel mit Nase
DIN 1810 Form A
für Nutmütern nach DIN 1804,
Spezial-Stahl, angelassen, schwarz

Hook wrenches with nose
DIN 1810 Form A
for slotted nuts as per DIN 1804,
special steel, tempered, black



260 S

Artikel-Nr. Order-No.	Ident-Nr. Ident-No.	mm	L		
260 S	04534	12/ 14	110	25	10
260 S	04544	16/ 20	110	25	10
260 S	04554	25/ 28	136	45	10
260 S	04564	30/ 32	136	50	10
260 S	04574	34/ 36	170	90	10
260 S	04584	40/ 42	170	90	10
260 S	04594	45/ 50	206	155	10
260 S	04604	52/ 55	206	160	10
260 S	04614	58/ 62	242	255	10
260 S	04624	68/ 75	242	255	10
260 S	04634	80/ 90	280	410	10
260 S	04644	95/ 100	280	385	10
260 S	04654	110/ 115	335	745	I
260 S	04664	120/ 130	335	720	I
260 S	04674	135/ 145	385	1000	I
260 S	04684	155/ 165	385	965	I
260 S	04694	180/ 195	470	1580	I
260 S	04704	205/ 220	470	1580	I
260 S	04714	230/ 245	560	2250	I
260 S	04724	260/ 270	568	2250	I
260 S	04734	280/ 300	680	5000	I
260 S	04744	380/ 400	770	6700	I

Hakenschlüssel mit Zapfen
DIN 1810 Form B
für Kreuzlochmütern gemäß DIN 1816,
Spezial-Stahl, angelassen, schwarz

Hook wrench with pin
DIN 1810 Form B
for round nuts with pin holes as per DIN 1816,
special steel, tempered, black



265 S

Artikel-Nr. Order-No.	Ident-Nr. Ident-No.	mm	L		
265 S	04526	12/ 14	110	25	10
265 S	04536	16/ 18	110	40	10
265 S	04546	20/ 22	110	40	10
265 S	04556	25/ 28	136	55	10
265 S	04566	30/ 32	136	55	10
265 S	04576	34/ 36	170	100	10
265 S	04586	40/ 42	170	100	10
265 S	04596	45/ 50	205	165	10
265 S	04606	52/ 55	205	165	10
265 S	04616	58/ 62	240	270	10
265 S	04626	68/ 75	240	270	10
265 S	04636	80/ 90	280	410	10
265 S	04646	95/ 100	280	410	10
265 S	04656	110/ 115	335	780	I
265 S	04666	120/ 130	335	780	I
265 S	04676	135/ 145	380	1000	I
265 S	04686	155/ 165	380	1000	I
265 S	04696	180/ 195	470	1580	I
265 S	04706	205/ 220	470	1580	I
265 S	04716	230/ 245	560	2250	I
265 S	04726	260/ 270	570	2250	I